



B

NOTES:

- 1) MATERIAL: 6061-T6/T62 ALUMINUM SHEET, 0.250" THK
PER QQ-A-250/11 OR AMS-QQ-A-250/11
OR AMS 4025 OR AMS 4027
OR ASTM B209
REF DART SPEC M6061T6S0.250
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
PRIME PER DART QSI 005 4.2.1.3.3 AND PAINT WHITE PER DART QSI 005 4.2.2.4
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.010 TO 0.030 MAX
- 6) IDENTIFICATION: PER DART QSI 044 6.1
- 7) WEIGHT: 0.15 lbs
- 8) MASK HOLES PRIOR TO PAINT

D5496-1 CONNECTOR

RELEASED

2018 JUL 30 NO
ECN 18-749

APPROVED

B	REMOVED -041; REVISED NOTES; REVISED CENTER HOLE; REVISED PART HEIGHT (ZN D6-1)	VS	18.05.23
A	NEW ISSUE	VS	18.02.27
REV.	DESCRIPTION	BY	DATE
DESIGN	VS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	VS		
CHECKED	RF	DRAWING NO.	REV. B
MFG. APPR.	DD	D5496	SHEET 1 OF 1
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	CONNECTOR	NTS
DATE	18.05.23	COPYRIGHT © 2018 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	